

Rosenbauer – Central Division

One (1)

Production Specifications, rev. 1/7/05

One (1)
01-01-0100



DATE: 1/7/05

Prepared For:

DEPARTMENT NAME: Salyer V.F.D.

ADDRESS: P.O. Box 235

CITY: Salyer **STATE:** CA **ZIP:** 95563

FIRE CHIEF: David Murphy

PHONE: (530) 629-2073 **FAX:**

CELL PHONE: **EMAIL ADDRESS:**

CHASSIS MAKE: Freightliner **MODEL:** M2 112

ENGINE: Cat C13 410 HP **TRANSMISSION:** Allison 4000 EVS

WHEELBASE: 200", CA: 135"

MAXIMUM OVERALL LENGTH: 28' 6"

One (1)
1B-00-0500

WARRANTY

We warrant each new motorized fire apparatus manufactured by CENTRAL STATES FIRE APPARATUS for a period of ONE YEAR from the date of delivery, except for chassis and other components noted herein.

Under this warranty we agree to furnish any parts to replace those that have failed due to defective material or workmanship where there is no indication of abuse, neglect, unusual or other than normal service providing that such parts are, at the option of CENTRAL STATES FIRE APPARATUS, made available for our inspection at our request, returned to our factory or other location designated by us with transportation prepaid within thirty days after the date of failure or within one year from the date of

Rosenbauer – Central Division

delivery of the apparatus to the original purchaser, whichever occurs first, and inspection indicates the failure was attributed to defective material or workmanship.

The warranty on the chassis and chassis supplied components, storage batteries, generators, electrical lamps and other devices subject to deterioration is limited to the warranty of the manufacturer thereof and adjustments for the same are to be made directly with the manufacturer by the customer.

This warranty will not apply to any fire apparatus that has been repaired or altered outside our factory in any way, which in our opinion might affect its stability or reliability.

This warranty shall not apply to those items that are usually considered normal maintenance and upkeep services: including, but not limited to, normal lubrication or proper adjustment of minor auxiliary pumps or reels.

This warranty is in lieu of all other warranties, expressed or implied, and all other obligations or liabilities on our part. We neither assume nor authorize any person to assume for us any liability in connection with the sales of our apparatus unless made in writing by CENTRAL STATES FIRE APPARATUS.

One (1)
1B-00-2050

10 YEAR GALVANNEAL BODY WARRANTY

CENTRAL STATES FIRE APPARATUS (CSFA) warrants to the original purchaser only, that the all galvanneal body, fabricated by CENTRAL STATES FIRE APPARATUS, under normal use and with reasonable maintenance, will be structurally sound and will remain free from corrosion perforation for a period of TEN (10) years.

This warranty does not apply to the following items that are covered by a separate warranty: paint finish, hardware, moldings, and other accessories attached to this body. In addition, this warranty does not apply to any part or accessory manufactured by others and attached to this body.

CENTRAL STATES FIRE APPARATUS MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO THE GALVANNEAL BODY AND ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED.

CENTRAL STATES FIRE APPARATUS will replace without charge, repair or make a fair allowance for any defect in material or workmanship demonstrated to its satisfaction to have existed at the time of delivery or not due to misuse, negligence, or accident. If CENTRAL STATES FIRE APPARATUS elects to repair this body, the extent of such repair shall be determined solely by CENTRAL STATES FIRE APPARATUS, and shall be performed solely at the factory, or at an approved facility. The expense of any transportation to or from such repair facility shall be borne by the purchaser and is not an item covered under this warranty.

CENTRAL STATES FIRE APPARATUS will not be liable for consequential damages and under no circumstances will its liability exceed the price for a defective body. The remedies set forth herein are exclusive and in substitution for all other remedies to which the purchaser would otherwise be entitled.

CENTRAL STATES FIRE APPARATUS will be given a reasonable opportunity to investigate all claims. The purchaser must commence any action arising out of, based upon or relating to agreement or the breach hereof, within twelve months from the date the cause of the action occurred.

Rosenbauer – Central Division

One (1)
1B-00-3500

PAINT WARRANTY

The PPG paint performance guarantee will cover the areas of the vehicle finished with the specified product for a period of FIVE (5) years beginning the day the vehicle is delivered to the purchaser.

The areas as outlined on the Guarantee Certificate, will be covered for the following paint failures:

GUARANTEE INCLUSIONS:

FULL APPARATUS BODY MANUFACTURED AND PAINTED BY CENTRAL STATES FIRE APPARATUS:

- * Peeling or delamination of the topcoat and/or other layers of paint.
- * Cracking or checking.
- * Loss of gloss caused by cracking, checking, or hazing.
- * Any paint failure caused by defective PPG Fleet Finishes which are covered by this guarantee.

All guarantee exclusions, limitations, and methods of claims are covered in the full certificate provided to the original purchaser.

Rosenbauer – Central Division

One (1)
BS-10-3600

CHASSIS

A chassis shall be furnished per the attached specifications located in the chassis section of the bid proposal.

One (1)
CC-50-0510

STEP TYPE FUEL TANK

There shall be a step type fuel tank furnished with the chassis.

One (1)
CC-50-3500

CHASSIS AIR FILL CONNECTION

A quick disconnect male air-fill fitting is to be provided and installed near the drivers door entrance area. Air chuck is to be plumbed through a one way check valve, and connected to the proper air reservoir tank to fill the chassis air system. A matching female fitting is to be provided and shipped loose with the completed apparatus.

The air inlet shall be located near the driver's lower step well area of the cab.

One (1)
CC-50-5500

FRONT MUD FLAPS

Heavy-duty, black colored, rubber mud flaps shall be furnished and installed behind the front wheels of the vehicle. Mud flaps shall extend the full width of the front tires and are to be attached with stainless steel fasteners.

One (1)
CC-50-6000

REAR MUD FLAPS

Heavy-duty, black colored, rubber mud flaps shall be furnished and installed behind the rear wheels of the vehicle. Mud flaps shall extend the full width of the rear duals and are to be attached with stainless steel fasteners.

One (1)
CC-51-1100

HORIZONTAL CHASSIS EXHAUST

The chassis exhaust system shall be extended to the front of the right rear wheel.

One (1)
CC-51-1300

CHASSIS EXHAUST HEAT SHIELD

The chassis exhaust system shall have a heat shield installed where the exhaust pipe passes below the side compartments.

One (1)
CC-61-1000

DOME LIGHTS IN CHASSIS CAB

There shall be a dome light furnished on the ceiling of the chassis cab. The light(s) shall be controlled by individual switches located on each light.

Rosenbauer – Central Division

One (1)
CC-65-0400

The light shall have a red lens and be located directly above the officer's seat.

ALTERNATOR

The alternator shall be of adequate size to meet the NFPA requirements and to accommodate the specific apparatus electrical load.

Rosenbauer – Central Division

One (1)
DD-00-0850

WATEROUS CLVK-500 GPM SINGLE STAGE FIRE PUMP

The centrifugal type fire pump shall be a Waterous model CLVK midship mounted with a rated capacity of 500 GPM. The pump shall meet NFPA 1901 requirements. The pump shall have a PTO drive gearbox.

One (1)
DD-01-4400

SINGLE STAGE MIDSHIP MOUNTED FIRE PUMP

A Waterous Model CLVK fire pump shall be midship mounted, single stage centrifugal type. In addition to meeting NFPA 1901 requirements, it shall be constructed and mounted in accordance with the following specifications.

Fire pump shall incorporate direct mount, high strength, gear drive transmission.

Fire pump shall be driven by a heavy duty 10 bolt PTO capable of enough torque to operate the fire pump at rated capacity for continuous duty. The PTO shall be approved by Allison for this type of service. The PTO shall be of a "Hot Shift" style capable of either full capacity stationary pumping or pump and roll. Stationary pumping shall be done with chassis transmission in neutral. At time of delivery the pump shall be tested and rated as follows:

- 100% of rated capacity at 150 pounds net pressure
- 70% of rated capacity at 200 pounds net pressure
- 50% of rated capacity at 250 pounds net pressure
- 100% of rated capacity at 165 pounds net pressure

The pump casing shall be a three-piece, vertically split design, high strength gray iron.

The impeller shaft shall be stainless steel, heat treated, and precisely machined and ground to size. All bearings are to be oil or grease lubricated, ball-type, located outside the pump casing in the pump transmission, to accurately align and support the impeller shaft assembly and input shaft. Ball bearings are to be deep groove type, designed to carry both radial and axial loads. A face-type, self-adjusting, corrosion and wear resistant mechanical seal is to be provided.

The pump must be tested by the pump manufacturer for 10 minutes hydrostatically at a pressure of 500 psig. Certification by the pump manufacturer must be provided.

The pump shall be provided with a plate giving the rated flow at "capacity" and "pressure" test pressures, together with the R.P.M. of the engine at those pressures and deliveries and mounted in clear view of the pump operator's panel. Data plate shall include model and serial numbers of the pump body and chain transmission, hydro and discharge test pressures, and the date of pump and transmission manufacture.

All pump components including relief valve, pump shift and priming system shall be manufactured by the Waterous Company to insure sole source responsibility and engineered compatibility.

Rosenbauer – Central Division

PRIMING SYSTEM

The pump shall be capable of taking suction and discharging water with a lift of 10 feet in not more than 30 seconds with the pump dry, through 20 feet of suction hose of appropriate size. It shall be capable of developing a vacuum of 22" at an altitude of up to 1000 feet.

A vacuum test with a capped suction of at least 20' long shall develop 22" of vacuum and hold a vacuum with a drop not in excess of 10" in 5 minutes.

One (1)
DD-04-0070

VPE PRIMING SYSTEM

A high capacity, electrically driven Waterous model VPE rotary vane priming pump shall be provided mounted in the pump compartment.

The priming system shall include a one-gallon oil reservoir tank that is conveniently located behind a hinged access door. Priming tank shall be properly vented so as to provide priming pump lubrication.

One (1)
DD-04-0100

MANUAL CONTROL PRIMING PUMP

Priming pump shall be activated by a mechanical/electric valve with a single pull control located at the pump operator's panel area. Valve actuation may be accomplished while the main pump is operational, if necessary to assure a complete prime.

One (1)
DD-04-5000

MECHANICAL SHAFT SEAL

The pump shall be equipped with self-adjusting, maintenance free, "Mechanical Shaft Seal" which is designed to be functional in the unlikely event of a seal failure. Pumps with packing which requires periodic adjustment and/or replacement will not be acceptable.

One (1)
DD-04-7220

CLASS ONE GOVERNOR

Class 1, pressure governor for electronic engines shall be furnished and installed on the apparatus. The system shall include an alpha/numeric display to show pump pressure and engine RPM. The control panel shall include a RPM/PSI mode switch, an on/off power switch, increase and decrease switches for throttle control, a preset switch to select preset pressure or RPM, and an idle switch to return to idle. The pressure governor shall be connected to the electronic engine and maintain the specified preset discharge pump pressure or a preset engine speed.

The device will be furnished, installed and tested by the apparatus body builder.

One (1)
DD-04-7500

MANIFOLD DRAIN

A manifold drain valve shall be furnished with all pump drains connected to it so that the entire pump system may be drained by one control.

Drain valve assembly shall consist of a stainless steel plunger and a bronze body rigidly attached to the fire pump transmission.

Rosenbauer – Central Division

A control handle is to be provided and located below the driver's side running board of the pump house, properly identified as MASTER DRAIN.

One (1)
DD-99-0500

FIRE PUMP WARRANTY

The Waterous fire pump shall carry the pump manufacturer's five (5) year warranty covering defective parts and workmanship. A copy of the pump manufacturer's warranty policy shall be provided with the completed apparatus.

One (1)
DH-20-2000

PUMP COOLING LINE

A 3/8" cooling line shall be installed to recirculate water from the pump back to the water tank, to cool the pump during pro-longed pumping operations. The cooling line shall be controlled at the operator's position with a quarter turn valve.

One (1)
DH-20-5000

HEAT EXCHANGER

A heat exchanger shall be provided on the pump driving engine cooling system. The heat exchanger shall not allow mixing of the pump driving engine coolant and water from the fire pump.

A gated line shall be installed to provide water from the fire pump to the pump driving engine heat exchanger to assist in engine cooling during pumping operations. The heat exchanger line shall be controlled at the pump operator's panel.

One (1)
EE-01-1000

PUMP SHIFT INDICATOR LIGHTS

Fire pump shall be driven by a heavy duty 10 bolt PTO capable of enough torque to operate the fire pump at rated capacity for continuous duty. The PTO shall be approved by Allison for this type of service. The PTO shall be of a "Hot Shift" style capable of full capacity stationary pumping. Stationary pumping shall be done with chassis transmission in neutral. Pump engagement lights and safety interlock system for PTO driven pumps that are to be used for Stationary Pumping Only with the transmission in neutral shall be as follows:

- A "Pump Engaged" indicator light shall be provided both in the driving compartment and on the pump operator's panel to indicate that the pump shift has been successfully completed.
- An "OK to Pump" indicator light shall be provided in the driving compartment to indicate that the pump is engaged, the chassis transmission is in neutral, and the parking brake is engaged.
- A "Throttle Ready" indicator shall be provided at the pump operator's panel that is energized when the "OK to Pump" indicator is energized or when the chassis transmission is in neutral and the parking brake is engaged.
- An interlock system shall be provided to prevent advancement of the engine speed at the pump operators panel unless the chassis transmission is in neutral and the parking brake is engaged, or the apparatus is in "OK to Pump" mode.
- Controls to engage the PTO are to be in the cab, and easily accessible.

Rosenbauer – Central Division

One (1)
EE-01-2010

WATEROUS PTO PUMP INSTALLATION

The Waterous PTO fire pump shall be installed in conjunction with the body manufacturing process. Fire pump installation shall include installation of the fire pump, modification and/or fabrication of new drivelines and all pump-mounting brackets. PTO drive shaft(s) shall be spin balanced prior to final installation.

One (1)
EE-02-1000

INTAKE RELIEF VALVE

A 2-1/2" intake relief valve preset at 125 psi shall be permanently installed on the suction side of the fire pump. The valve shall have an adjustment range of 75 psi to 250 psi, and shall be designed to automatically self-restore to a non-relieving position when excessive pressure is no longer present.

Discharge side of the intake relief valve shall be plumbed to the right side below the running boards, away from the pump operator, and shall terminate with a 2-1/2" NST male chrome threaded adapter, marked with an engraved tag "Intake pressure relief outlet - Do Not Cap".

One (1)
EE-02-5100

HOT DIP GALVANIZED INTAKE MANIFOLD

The suction manifold shall be fabricated from heavy-duty tubular steel. The suction manifold shall have radiused sweep elbows to minimize water turbulence into the suction volute. The suction manifold shall be welded and pressure tested prior to the galvanizing process. After testing the entire suction manifold shall be hot dip galvanized to minimize corrosion. The hot dip galvanized suction manifold shall be attached to the pump intake volute with a heavy-duty, flexible victaulic coupling.

The hot dip galvanized manifold assembly shall have a ten (10) year warranty.

One (1)
EE-02-5180

DRIVERS SIDE STEAMER INLET

There shall be one (1) steamer inlet furnished on the driver's side of pump panel. The suction inlet shall have 4" NST thread. The suction inlet shall have a removable strainer provided inside the external inlet.

Steamer inlet to be as short as possible to allow suction fittings to be attached without extending past the side running boards.

One (1)
EE-02-5190

PASSENGER SIDE STEAMER INLET

There shall be one (1) steamer inlet furnished on the passenger side of pump panel. The suction inlet shall have 4" NST thread. The suction inlet shall have a removable strainer provided inside the external inlet.

Steamer inlet to be as short as possible to allow suction fittings to be attached without extending past the side running boards.

The suction tubes shall be short to allow for installation of adapters without excessive overhang.

Rosenbauer – Central Division

One (1)
EE-20-0500

SUCTION CAP DRIVER'S SIDE

The driver's side suction inlet shall be equipped with a chrome-plated, long handled, cap capable of withstanding 500 PSI.

One (1)
EE-20-1000

SUCTION CAP PASSENGER SIDE

The passenger's side suction inlet shall be equipped with a chrome-plated, long handled, cap capable of withstanding 500 PSI.

One (1)
ES-02-1500

2-1/2" GATED SUCTION INTAKE DRIVER SIDE

A 2-1/2" independent gated suction intake shall be provided on the driver's side pump panel. Intake shall be provided with a quarter-turn valve and control. The intake shall have a 3/4" drain valve with handle. Each intake shall have chrome-plated female swivel adapter with removable internal screen and a chrome-plated plug type cap with end chain.

One (1)
ES-02-1510

SUCTION VALVE CONTROL

Suction valve shall have swing type control handle located adjacent to valve.

One (1)
ES-04-0000

TRIM PANEL

A bolt on stainless steel trim panel shall be provided for easy access to the valve for repair or removal without removing the side panel on all intakes and discharges.

One (1)
FA-00-1000

HOT DIP GALVANIZED DISCHARGE MANIFOLD

The discharge manifold shall be fabricated from heavy-duty tubular steel. The discharge manifold shall be fabricated, welded, all fittings attached and pressure tested prior to the galvanizing process. After testing the entire suction manifold shall be hot dip galvanized to minimize corrosion. The hot dip galvanized discharge manifold assembly shall be bolted to the pump and have stabilizer arms attached to reinforce the discharge manifold.

The hot dip galvanized manifold assembly shall have a ten (10) year warranty.

One (1)
FA-01-0000

PUMP DISCHARGES

Each gated discharge outlet shall include an Akron heavy-duty brass, quarter-turn, swing-out ball valve. All lines to have victaulic couplings or hose with stainless steel fittings installed where flex may occur to prevent cracking of the plumbing system. Each discharge shall have 3/4" cast bronze 1/4 turn drain valve complete with reinforced teflon seals, and blowout proof stem rated to 600 psi. A chrome-plated zinc handle shall be provided on each drain valve, complete with a 1" X 1 1/2" recessed identification label. Drains shall be aligned in a straight horizontal row at the lower edge of the

Rosenbauer – Central Division

corresponding pump panel so as to allow for ease of identification and operation. Each drain shall be labeled and numbered to correspond to the respective discharge outlet and coloring.

Individual discharge controls are to be aligned in a straight horizontal row across the pump operator's control panel, directly in-line with the corresponding discharge outlet line pressure gauges.

One (1)
FA-01-0010

GALVANIZED PLUMBING

All rigid piping five-inch diameter or less shall be galvanized type with tapered thread or victaulic type couplings.

One (1)
FA-01-0500

DRIVER SIDE DISCHARGE OUTLET

Each 2-1/2" discharge outlet on the driver's side pump panel shall have a 2-1/2" quarter turn valve with control on pump operator's panel. There shall be a chrome plated 2-1/2" NST adapter that extends through the pump panel. Each discharge shall be provided with chrome-plated 30-degree discharge elbow.

One (1) 2-1/2" discharge shall be provided on the driver's side pump panel.

One (1)
FA-01-0501

MANUAL VALVE

Discharge valve shall be swing-out type with manual control handle located on pump operator's panel.

One (1)
FA-01-0510

MANUAL DRAIN VALVE

The driver's side 2-1/2" discharge outlet shall have a 3/4" drain with individual control on side pump panel.

Drain valve shall be a Class1, quarter turn type.

One (1)
FA-01-1000

PASSENGER SIDE DISCHARGE OUTLET

Each 2-1/2" discharge outlet on the passenger's side pump panel shall have a 2-1/2" quarter turn, swing-out valve with control on pump operator's panel. There shall be a chrome-plated 2-1/2" NST adapter that extends through the pump panel. Each discharge shall be provided with chrome-plated 30-degree discharge elbow.

One (1) 2-1/2" discharge shall be provided on the passenger's side pump panel.

One (1)
FA-01-1001

MANUAL VALVE

Discharge valve shall be swing-out type with manual control handle located on pump operator's panel.

Rosenbauer – Central Division

One (1)
FA-01-1010

MANUAL DRAIN VALVE

The passenger's side 2-1/2" discharge outlet shall have a 3/4" drain with individual control on side pump panel.

Drain valve shall be a Class1, quarter turn type.

One (1)
FA-01-1500

DRIVER SIDE REAR DISCHARGE OUTLET

There shall be one (1) 2-1/2" discharge outlet located on the driver's side rear of the body below the hose bed. The discharge outlet shall have a 2-1/2" quarter turn, swing-out valve with control on pump operator's panel. There shall be a chrome-plated 2-1/2" NST adapter that extends through the rear of the body. The discharge shall be provided with a chrome-plated 30-degree discharge elbow.

One (1)
FA-01-1501

MANUAL VALVE

Discharge valve shall be swing-out type with manual control handle located on pump operator's panel.

One (1)
FA-01-1510

MANUAL DRAIN VALVE

The driver's side rear 2-1/2" discharge outlet shall have a 3/4" drain with individual control on side pump panel.

Drain valve shall be a Class1, quarter turn type.

Three (3)
FA-01-3220

2-1/2" CAPS AND CHAINS

The following discharge outlets shall be equipped with a 2-1/2" chrome-plated cap and chain.

One (1)
FC-31-0100

1-3/4" CROSSLAY(S) ASSEMBLY ABOVE PUMP

Crosslay hose bed(s) shall be designed to carry 200 feet of 1-3/4" double jacket fire hose. Crosslay hose bed(s) shall be located above the fire pump. The floor of the crosslay hose bed(s) shall be perforated to allow for drainage. Polished stainless steel hose roller assemblies shall be provided at the sides and lower edges of the crosslay opening on each side of the apparatus body.

Crosslay discharge(s) shall be plumbed using rigid pipe or flexible high-pressure hose coupled with stainless steel fittings. The crosslay shall be provided with 2" brass valve, and a 2" 90 degree swivel adapter with 1-1/2" NST male outlet thread.

One (1) 1-3/4" crosslay shall be provided.

Rosenbauer – Central Division

One (1)
FC-31-0101

MANUAL VALVE

Each discharge valve shall be swing out type with manual control handle located on pump operator's panel.

One (1)
FC-31-0108

MANUAL DRAIN VALVE

Each crosslay/speedlay shall have a 3/4" drain with individual control on side pump panel.

Drain valve shall be a Class1, quarter turn type.

One (1)
FC-31-4200

CROSSLAY HOSEBED COVER

A .125 polished aluminum treadplate hinged cover shall be provided over the crosslay hose bed(s) complete with full length stainless steel piano hinge and with chrome plated lift handles provided on each side of the cover. Stops shall be provided to hold the cover in the open position or to protect cab or other adjacent body components. The hinge shall be located on the forward section of the cover, closest to the chassis cab.

Latches shall be provided for the crosslay cover. Chrome grab handles shall be provided on each end.

One (1)
FC-31-4700

CROSSLAY END CAPS

A vinyl coated nylon cover shall be provided over each end of the crosslay hose bed. The vinyl end covers shall be held in place with velcro fasteners.

Flaps shall be red in color. Lift-a-dot type fasteners shall be provided for the end flaps.

One (1)
FH-03-0100

TANK TO PUMP PLUMBING

A 3" Akron ball type gated suction valve shall be furnished from the tank to the pump, complete with a flexible connection and enclosed in the pump compartment.

A check valve shall be provided and installed in the line between the tank and the pump to prevent the possibility of backfilling the booster tank through the tank to pump suction line.

Tank suction shall be located in a sump assembly located below the bottom of the tank, properly baffled to prevent surging of water. A 3" cleanout plug shall be provided in the bottom of the tank sump.

Rosenbauer – Central Division

One (1)
FH-03-6290

TANK FILL/COOLING LINE

A gated discharge line from the pressure side of the pump to the tank shall be furnished so the tank can be filled from draft or hydrant. Valve shall have control on the operator's panel. The valve is to be three-inch (3"), swing out type ball valve and be plumbed to tank with flexible type hose.

Rosenbauer – Central Division

One (1)
FJ-00-0406

HOT DIP GALVANIZED BOOSTER TANK

The booster tank shall be constructed of hot dip galvanized 10-gauge steel with 7-gauge steel end heads and bottom. Booster tank shall be of a "T" shape and design to allow for maximum compartmentation. Tank manufacturer shall provide a twenty (20) year warranty against defects in materials or workmanship to the original owner.

Tank shall have a bolted on, removable top for inspection and clean out of all tank compartments. Removable top shall be bolted on with corrosion resistant external bolts. Bolts are not to be in contact with the contents of the tank. There shall be a reusable gasket between the tank and cover. Booster tank shall be provided with proper splash baffles according to the latest edition of NFPA pamphlet 1901. All baffles are installed with the top flange of the baffles flush to the inner side of the fully removable lid to insure support for any hose bed weight load.

The tank shall be removable from the body without disturbing the body side panels. The booster tank shall be mounted on a steel sub frame. The steel sub frame shall consist of longitudinal 3" x 4.1# channels, and 3" x 4.1# transverse channels to provide bottom support. The cradle shall be installed to prevent fore/aft and side to side movement of the tank. The booster tank shall rest on rubber pads to isolate the tank frame from the body sub frame.

There shall be a minimum of a 4" overflow to discharge under the tank and behind the rear axle. Sump to be 10" x 6 x 6" and have a 3" clean out plug. The sump shall have an anti-whirlpool baffle plate attached on the topside. Fill opening shall have a hinged lid and an open release if the tank is filled at an excess rate. Fill opening shall have a hinged stainless steel screen to prevent any objects from dropping into the tank.

One (1)
FJ-02-6600

BOOSTER TANK

A 3000-gallon hot dip galvanized booster tank shall be provided.

One (1)
FJ-02-7610

BOOSTER TANK SUBFRAME

The booster tank shall be mounted on a steel sub frame. Steel sub frame shall consist of two (2) longitudinal 3" x 4 pound channels and two (2) 3" x 4 pound channels welded together to form a tank retention cradle. The tank retention cradle shall prevent fore and aft, and side to side movement of the tank. Additional 3" x 4 pound transverse cross member channels shall be installed to support the floor of the booster tank. The cross members shall have a maximum spacing of 20" for the polypropylene tanks. There shall be an additional full-length longitudinal member installed in the center of the tank support area. The booster tank shall rest on heavy rubber channels that isolate the polypropylene tank from the sub frame.

One (1)
FJ-04-7000

EXTERNAL TANK FILL

An external tank fill shall be provided and installed at the rear of the body. The tank fill shall include a quarter turn 2-1/2" Akron ball valve with a chrome-plated female swivel, plug and chain.

The tank fill shall be located on the passenger's side.

A 30 degree 2.50" chrome plated elbow shall also be provided.

Rosenbauer – Central Division

REAR TANK DUMP VALVE

One (1) 10.00" Bray tank dump valve (or equal), series 30 will be installed at the rear of the water tank. The valve will have 316 stainless steel stem and disc and EPDM seat. The valve will be actuated pneumatically from one (1) switch inside the cab and one (1) switch at the rear of the apparatus. A manual override will be provided at the valve.

A 90 degree, one piece dump chute will be provided. The chute will be reversible to dump from both sides and removable for storage. The chute will extend past the body side for dumping.

A chute support system will also be provided. It will be constructed of 2.00" x 2.00" aluminum tubing. Two (2) "receiver style" mounts will be installed under the tailboard to allow the support system to be used for dumping to either side of the truck. The support will store under the tailboard. A locking pin will be provided.

One (1)
FK-01-0500

DRIVER SIDE MOUNTED OPERATOR'S CONTROL PANEL

All pump suction and discharge controls are to be mounted on the driver side pump operator's panel so as to permit operation of the pump from a central location.

All of the pump controls shall be clearly identified with permanently engraved plate type labels.

A full panel width polished light hood with a minimum of three Weldon model 2025 light assemblies shall be provided to illuminate the entire pump operator's control panel.

An additional polished light hood with a minimum of two Weldon model 2025 light assemblies shall be provided to illuminate the right side pump panel. Lights shall be controlled by the operator's panel light switch.

GAUGE PANEL

All gauges shall be suitably enclosed and mounted on a full pump compartment width "hinged" gauge panel constructed of the same material as the pump operators control panel, allowing access to the backside of all gauges and gauge lines. Panel is to include a stainless steel piano hinge, flush mounted chrome plated trigger latch, and stainless steel cable end stops. Electrical wiring and all gauge lines shall be properly tie wrapped to prevent kinking or cutting of the lines when the panel is opened.

One (1)
FK-01-1600

EXTRUDED ALUMINUM PUMP HOUSE STRUCTURE

The pump house structure shall be fabricated of extruded aluminum. The structure shall be welded together and have gusset plates on each corner. The pump house shall be mounted separate from the body and chassis and be bolted to the chassis frame rails.

The exposed areas of the pump house structure shall be overlaid with polished aluminum treadplate.

Rosenbauer – Central Division

One (1)
FK-01-2100

PUMP PANEL PUMP ENGAGEMENT LIGHT

One (1) light in the control panel light hood shall come on with a successful pump engagement. This shall be in addition to the "OK to Pump" light on the control panel.

One (1)
FK-01-2400

PUMP PANELS

The right and left side pump panels shall be constructed entirely of black vinyl covered aluminum material. The left side panel shall be completely "bolted" in place for ease of removal and the right side panel shall be supplied with removable lift and turn type fasteners.

One (1)
FK-01-3000

PUMP COMPARTMENT ACCESS DOOR

The passenger's side pump panel shall be provided with a full panel width vertically hinged access door located in the upper portion of the side panel. This door shall be approximately 18" high and as wide as possible, and shall be constructed of polished aluminum treadplate. Two (2) flush mounted, push type latches shall be furnished to hold the door closed. The inspection door shall be attached with a stainless steel hinged and have a retainer cable attached to prevent the door from opening too far.

One (1)
FK-01-5500

DUNNAGE OVER PUMP

There shall be a dunnage compartment furnished above the pump. The dunnage compartment shall be as wide as possible from side to side, and be a minimum of 12" deep. The floor shall be bolted in place and removable for access to the pump.

An aluminum treadplate cover shall be installed over the dunnage compartment. A latch shall be provided to hold the cover in place when in the down position. Gas cylinders shall be provided to hold the cover in the open position.

Chrome grab handles shall be provided at each end for opening and closing the cover, and a foam rubber gasket where the cover comes in contact with a painted surface.

One (1)
FK-10-0000

PUMP OPERATORS PANEL

The following equipment shall be installed on the pump operator's panel.

One (1)
FK-10-2000

INDIVIDUAL MASTER GAUGES

NOSHOK 4" pressure gauges shall monitor the master pump intake and master pump discharge pressures. They shall be located on the pump operator's panel and located close to each other with the intake gauge to the left of the pump discharge gauge. The master intake gauge shall read from 30" vacuum to 400-psi while the master discharge gauge shall read from 0-psi to 400-psi. The construction shall be heavy-duty, reinforced stainless steel case with a machined brass stem connection solidly bolted to the stainless steel case. The pointer in each gauge will have an orange tip for increased visibility. The gauges facing the plate cover shall be white with black numbers.

Rosenbauer – Central Division

One (1)
FK-10-2740

PRESSURE GAUGES

Noshok, 2-1/2" diameter liquid filled pressure gauges shall be provided. The gauges are to have white faces with black lettering. Line pressure gauges shall be individually identified with engraved labels.

Individual line pressure gauges are to be mounted adjacent to the corresponding discharge valve control.

One (1)
FK-10-2900

There shall be one (1) pressure gauge for each 1-1/2" discharge outlet.

Three (3)
FK-10-3000

There shall be one (1) pressure gauge for each 2-1/2" discharge outlet.

One (1)
FK-11-2520

CLASS ONE GOVERNOR

Class 1, pressure governor for electronic engines shall be furnished and installed on the apparatus. The system shall include an alpha/numeric display to show pump pressure and engine RPM. The control panel shall include a RPM/PSI mode switch, an on/off power switch, increase and decrease switches for throttle control, a preset switch to select preset pressure or RPM, and an idle switch to return to idle. The pressure governor shall be connected to the electronic engine and maintain the specified preset discharge pump pressure or a preset engine speed.

The device will be furnished, installed and tested by the apparatus body builder.

One (1)
FK-12-0900

INFORMATION CENTER

A Class 1 Enfo IV master engine gauge and warning device shall be furnished and installed on the pump operator's panel. The Class 1 Enfo IV is equipped with super bright displays for maximum visibility during daytime hours. The device will monitor the following engine systems;

- Engine RPM display
- System voltage display
- Engine oil pressure display
- Engine water temperature display

One (1)
FK-12-3800

PUMP HOUR METER

A pump hour meter shall be provided on the pump operator's panel.

One (1)
FK-12-5200

PUMP PANEL IDENTIFICATION LABELS

All discharges shall be provided with color-coded labels. Identification labels shall be provided at the discharge control, the discharge outlet, and at the discharge drain valve control, color-coded according to NFPA recommended standards.

Rosenbauer – Central Division

One (1)
FK-12-7100

PUMP PANEL WATER TANK LEVEL GAUGE

A Class One ITF Intelli-tank water tank level gauge shall be provided on the pump operator's panel. The Intelli-tank display features wide angle viewing and four (4) ultra-bright LED's for high visibility, even in direct sunlight. The Intelli-tank utilizes a pressure transducer, ILO of probes, to provide nine (9) accurate levels of indication.

One (1)
FK-13-1500

UL TEST CONNECTIONS

A pump pressure and vacuum test block assembly shall be provided and mounted at the pump operator's control panel. The test block assembly shall include plug type caps.

Rosenbauer – Central Division

One (1)
HA-00-0200

HOSE BODY

The apparatus hose body is to be properly reinforced without the use of angles or structural shapes, and free from all projections that might injure the fire hose.

The main apparatus hose body shall run the full length of the apparatus body from behind the pump panel area to the rear face of the body.

The upper rear interior of the beavertail extrusions on the right and left side shall be overlaid with brushed stainless steel to protect the painted surface from damage by hose couplings

One (1)
HA-00-0320

HOSE BED CAPACITY

The hose bed will be configured to be 55 cubic feet, unless the desired hose load requires more area.

Exact hose bed requirements shall be determined prior to construction.

One (1)
HA-00-0400

HOSE BED FLOORING

Floors of the hose beds are to be provided with removable slat style extruded aluminum hose bed gratings, spaced 1/2" apart for proper hose ventilation. Hose bed gratings are easily lifted out of the main hose bed for access to the top of the specified booster water tank.

One (1)
HA-00-1600

MAIN HOSE BED DIVIDER

Adjustable hose bed dividers shall be provided in the main hose bed.

The hose bed divider(s) shall be fabricated of 1/4" smooth aluminum sheet stock, welded into a "T" shaped aluminum extrusion for added strength along the bottom edge of the divider.

The divider shall be fully adjustable, mounted using aluminum "C" channel tracks at the front and rear of the divider for full side to side adjustment.

One (1) hose bed divider shall be provided.

One (1)
HD-00-5850

HARD SUCTION HOSE STORAGE COMPARTMENT

There shall be a storage compartment, large enough to accommodate two (2) hard suction hoses, shall be provided in the upper "T" of the booster tank. The design shall allow the hose to be individually removed from the rear of the apparatus. The hard suction hose compartment shall have aluminum treadplate door with stainless steel hinge and push to latch door catches.

The compartment shall be located on the driver's side of the body. The compartment shall accommodate two (2) 4" x 10 ft. sections of light weight PVC suction hose and strainer.

Rosenbauer – Central Division

One (1)
HD-00-7015

HARD SUCTION HOSE FURNISHED BY BODY BUILDER

The hard suction hose shall be furnished by the body builder. See equipment section of this document for make and model of hard suction hose.

One (1)
HD-05-0200

FOLDING TANK STORAGE COMPARTMENT

A vertical storage area shall be provided on the passenger side of the booster tank and below the hose bed to carry a portable folding tank. Compartment shall be provided with poly slides on each side, mounted to the floor, to hold the folding tank in position. There shall be a hinged treadplate door with push button latch on rear for ease in loading and removing the folding tank.

One (1)
HD-05-1035

FOLDING TANK CAPACITY

The folding tank compartment shall contain the 4000 gallon folding water tank as later specified.

One (1)
KB-02-1000

APPARATUS BODY

The apparatus body compartments shall be fabricated of twelve gauge A-60 Galvanneal steel.

The side compartments shall be an integral assembly with the rear fenders.

Circular fender liners shall be provided for prevention of rust pockets and ease of maintenance.

Compartment floors shall be of the sweep out design with the floor higher than the compartment door lip.

Drip protection shall be provided above the doors by means of bright aluminum extrusion or formed bright aluminum treadplate.

The top of the compartment shall be covered with bright aluminum treadplate formed over the edges on the front, rear and outward side. The corners of the aluminum covers shall be "TIG" welded.

All screws and bolts that protrude into a compartment shall have acorn nuts installed to prevent injury and snagging.

FASTENERS

All aluminum and stainless steel components shall be attached using stainless steel fasteners.

Compartment door hinges, handrails and running boards shall be attached using minimum 1/4" diameter machine bolt fasteners.

3/16" diameter fasteners shall only be used in nonstructural areas such as; door handles, trim moldings, gauge mounting, etc.

Rosenbauer – Central Division

One (1)
KB-10-4400

BODY DIMENSIONS

The tandem axle body shall be 102" wide, reference sales drawing for actual length and height dimensions.

One (1)
KK-01-1100

APPARATUS BODY SUB-FRAME

The apparatus body sub frame shall be constructed entirely of heavy steel structural channel material.

Two full frame lengths, three-inch (3") 4 pound per foot longitudinal steel channels shall form the sides of the body sub frame and sides of the water tank cradle. Sub frame cross members shall be fabricated with three inch (3") 4 pound per foot heavy steel channel cross members welded to the longitudinal body sub frame sides and the full length frame pads.

Two full frame length 1/2" x 3" flat steel frame pads shall be attached to the body sub frame and rest on top of the chassis frame rails for proper frame weight distribution.

The steel frame pads, longitudinal steel channels and sub frame cross members shall be attached to the chassis frame rails using heavy "U" bolt fasteners to allow removal of the sub frame and body assembly from the chassis. There shall be a barrier provided between the sub frame and body to prevent electrolysis.

A minimum of two rear platform support channels shall be provided and constructed of 4.3 lb. per foot heavy steel material. Each support channel shall have welded in gusset where the support meets the rear sub frame rails.

One (1)
KK-02-0400

COMPARTMENT VENTS

All body compartments shall have a minimum of one (1) louvered panel bolted into a wall to provide the proper airflow inside the compartment. There shall be a filter installed behind the louvered panel. The filter shall be accessible for cleaning by removing the louvered panel on the interior of the compartment.

One (1)
KK-02-0500

BODY AND PUMP HOUSE FLEX JOINT

When equipped with a fire pump, the body and pump house shall be a separate freestanding component forming a true flex joint between the body and pump house. The intent is to allow either to be easily removed as a single unit without disturbing the other and to provide a flex joint between the two modules. Designs where the pump house and body are interjoined as a common unit do not meet the technical requirement of providing a flex joint or the repairability requirement of these specifications.

One (1)
KK-02-0654

WHEEL WELL LINER AND FENDERETTES

For ease of accessibility and maintenance, wheel well panels shall be double break formed painted smooth plate that is welded in place.

Rosenbauer – Central Division

To fully protect the wheel well area from road debris and to aid in cleaning, a full depth (minimum of 25") radius wheel well liner shall be provided. Wheel well liner shall be smooth galvalneal steel to prevent corrosion.

The rear wheel wells shall be radius cut for a streamlined appearance. A polished aluminum fenderette shall be furnished at each rear wheel well opening, held in place with concealed stainless steel fasteners.

One (1)
KK-02-3700

REAR TOW EYES

There shall be two tow eyes furnished under the rear of the body and attached directly to each chassis frame rail. There shall be a reinforcement spreader bar connecting the two tow eyes. Tow eyes are to be constructed of 3/8" plate steel with a 4" I.D. hole, large enough for passing through a tow chain end hook.

One (1)
KK-03-0050

APPARATUS COMPARTMENTATION

There shall be large enclosed compartments on both sides of the body, starting at the front of the hose body and continuing to the rear of the apparatus. These compartments shall be as large as possible, using all available space.

The aluminum treadplate compartmentation tops on each side of the body shall be extended out and downwards a minimum of .50" over the compartment doors forming a drip rail. Corners shall be TIG welded.

Lower or rear face compartments, if specified shall be provided with polished aluminum drip rails.

One (1)
KK-03-0065

HINGED COMPARTMENT DOOR CONSTRUCTION

All hinged compartment doors shall be of the flush style so that the entire door fits flush against the apparatus body sides. Doors shall be designed, in the closed position, to have the painted edges protected from damage on the tops by forming the treadplate compartment tops into a extended drip edge, on the bottoms by the rub rail.

Doors shall be a minimum 2" thick, fabricated of a minimum of .125 smooth aluminum. Full panel inner compartment door liners shall be provided and constructed of smooth aluminum. The compartment doors shall have a foam panel glued in place between the exterior and interior door skin. Exterior door panels shall be smooth with no welds visible on the exterior skin. Double door compartments shall be equipped with a secondary latch to hold the secondary door in position.

All compartment door hinges shall be full-length piano type constructed of a minimum 14-gauge type 304 polished stainless steel with 3/16" stainless steel hinge pin with dual directional bolt holes for ease of adjustment.

When horizontally hinged lift-up doors are specified, they shall be equipped with heavy-duty gas filled props to hold the doors in the open position. All other hinged doors shall be equipped with spring loaded hold open device specifically designed for use on vertically hinged doors. Door holders shall be bolted in position. The door ajar switches shall be fully enclosed within structural members and shall not extend into the clear door opening.

Rosenbauer – Central Division

All compartment doors shall be provided with hollow core weather stripping to provide a weather tight seal at the door opening and to prevent road spray and debris from entering the compartment.

One (1)
KK-03-0076

EXTERIOR DOOR LATCHES

Side exterior compartment doors shall be furnished with a large stainless steel spring loaded D-handle with slam type latches. D-handles shall have the large "bent" D-ring for ease of grabbing the handle even when wearing mitts or gloves.

A non-moisture absorbing gasket shall be installed between the door latch and the door skin panel.

One (1)
KK-03-6700

DRIVER SIDE COMPARTMENTS

Two body compartments shall be furnished as follows:

- One compartment ahead of the rear wheels with double hinged doors.
- Full depth fender and wheel well liner over tandem rear axle.
- One compartment behind the rear wheels with single hinged door.

One (1)
KK-04-6700

PASSENGER SIDE COMPARTMENTS

Two body compartments shall be furnished as follows:

- One compartment ahead of the rear wheels with double hinged doors.
- Full depth fender and wheel well liner over tandem rear axle.
- One compartment behind the rear wheels with single hinged door.

One (1)
KK-50-0700

REAR BODY CONFIGURATION

Rear apparatus body compartments shall be as follows:

- There shall be one lower compartment with a single hinged drop-down door, between the frame rails supplied. This compartment shall extend in depth the last cross member on the frame.

One (1)
KK-50-4200

FLAT BACK BODY

The rear vertical surface of the body shall be flat from side to side.

One (1)
KL-30-0100

REAR ACCESS LADDER

Access to the top of the body from the rear driver's side area shall be from a heavy duty ladder, constructed from aluminum extruded tubing with rubber covered solid aluminum rungs.

Rosenbauer – Central Division

The exact location and design of the ladder shall be determined prior to construction.

Three (3)
KM-49-1615

SLIDE-OUT TRAY

Slide-out trays shall be constructed of 3/16" aluminum material. Trays shall have with heavy-duty roller bearing slides with a latch to hold the tray in the "open" and "closed" positions. Tray shall have capacity of 500 pounds.

Three (3) slide-out trays shall be provided.

The tray locations shall be one on the floors of the compartments in front of the rear wheels, each side, and one in the rear compartment.

One (1)
KR-01-0100

EXTRUDED ALUMINUM RUB RAILS

Full body length polished aluminum rub rails shall be bolted in place on the right and left body sides and in the pump panel area. The rub rails shall extend outward beyond the body sides for protection of the compartments and doors. There shall be a bolt on aluminum corner casting on each rear corner to blend the rear tailboard assembly with the side rub rails.

The side rub rails shall be a heavy extruded aluminum "C" channel.

One (1)
KR-04-0002

SIDE AND REAR OVERLAYS

Overlay panels shall be constructed of 3003 polished aluminum treadplate. Polished aluminum overlay shall be provided and installed in the following areas:

- The front face of each side compartment.
- The rear body face and vertical area above tailboard and below hose bed.
- Driver's side and passenger compartment top extending down over side to the compartment doors then forming a drip rail above doors.
- Front face of hose bed above booster tank.

Overlay shall be installed with "Aluminized" stainless steel bolts to prevent corrosion.

One (1)
KR-04-3000

SLIP-RESISTANT WALKWAY SURFACE

All exterior surfaces designated as stepping, standing, and walking areas shall have an aluminum slip-resistant overlay material installed. The slip-resistant overlay material shall have a raised serrated surface that will allow moisture to drain out either side. The recessed surface shall be one piece solid material to prevent road spray and debris from entering the top surface from below. The slip-resistant overlay material shall meet the requirements of NFPA 13-7.3. The slip-resistant surface shall be installed in the following areas of the apparatus body:

- Step areas of the side running boards.
- Rear step running board step.
- Walkway and standing platforms

Rosenbauer – Central Division

One (1)
KR-04-4902

REAR STEP/RUNNING BOARDS

The apparatus body running boards and rear step shall be constructed with slip-resistant surface and shall have bright aluminum treadplate trim around the outside edges. Side running boards and rear step shall be removable for ease of service in case of damage.

One (1)
KR-04-4908

REAR STEP/TAILBOARD

A single piece .188 rear step/tailboard shall be furnished that is a minimum of 12.00" deep and full width of the apparatus body, from rub rail to rub rail. The tailboard shall be provided with a removable casting on each corner for a pleasing appearance.

One (1)
KR-10-0000

HANDRAILS

Access handrails shall be 1 1/4" in diameter extruded aluminum with rubber insert. Access rail escutcheons and brackets shall be chrome plated and attached with stainless steel bolts. Anchoring of posts and framing members for railings of all types shall be of such construction that the completed railing structure shall be capable of withstanding a load of at least 225 pounds applied in any direction at any point along the rail.

One (1)
KR-10-0100

REAR HANDRAILS

Two (2) vertical access handrails shall be provided and mounted on the rear of the apparatus body, one on each side. Each rear handrail to be approximately 48" long.

One (1)
KR-10-0600

HANDRAILS

An access rail shall be provided and installed on the upper section of the right side pump house.

One (1)
KR-10-0700

HANDRAILS

An access rail shall be provided and installed on the upper section of the left side pump house.

Six (6)
KS-01-0100

FOLDING ACCESS STEPS

Six (6) NFPA approved folding steps shall be provided and mounted. All access steps shall have a minimum surface area of 35-square inches, and have a slip-resistant standing surface. The step shall be capable of supporting a 500-lb. load.

The locations of the steps shall be determined at the pre-construction conference.

Rosenbauer – Central Division

One (1)
NA-00-0010

ELECTRICAL

Electrical wiring, hydraulic lines, air system tubing, and control cables shall be fastened to the frame or body structure of the apparatus and shall be furnished with protective looms, grommets, or other devices, so that any such connector and/or wiring will be protected from shear or tear.

The body 12-Volt electrical system shall be designed specifically for the apparatus body. Automatic reset circuit breakers shall be provided and installed in all circuits.

Wiring data shall be provided with the completed apparatus.

Corrosion preventative compound shall be applied to all terminal plugs located outside of the cab or body where non-waterproof connections are located. All lights that have their sockets in a weather exposed area shall have corrosion preventative compound added to the socket terminal area.

The following electrical equipment and lights shall be provided and installed:

One (1)
NA-00-0080

WIRING SYSTEM

All electrical wiring shall be 14-gauge heavy strand copper with type GXL crosslink high temperature insulation, being circuit function printed every three-inches along its entire length.

Wiring data shall be provided with the completed apparatus.

The following electrical equipment and lights shall be provided and installed:

One (1)
NA-00-1000

TAIL & STOP LIGHTS

Two (2) Weldon #2010 rectangular red stop/tail lights shall be provided and mounted at the rear of the body, one on each side.

One (1)
NA-00-2500

DIRECTIONAL LIGHTS WELDON 2010

Two (2) Weldon #2010, rectangular amber directional signal lights with black arrows shall be provided and mounted at the rear of the body, one on each side below the stop/tail lights.

One (1)
NA-00-4000

BACKUP LIGHTS WELDON 2010 (RECT)

Two (2) Weldon #2010, rectangular clear backup lights shall be provided and mounted, one on each side at the rear of the body. The backup lights shall be mounted below the rear stop/tail and directional lights.

Rosenbauer – Central Division

One (1)
NA-00-5200

TAIL LIGHT TRIM

A polished cast aluminum three hole taillight bezel/housing shall be provided. The specified rear lighting units shall be installed in the bezel/housing and secured. The completed assembly is to be bolted to the apparatus body, one each side.

One (1)
NA-00-5300

CLEARANCE LIGHTS

There shall be clearance marker lights installed meeting all DOT requirements. The vehicle clearance lights shall be recess mounted within the rear center tailboard step.

One (1)
NA-00-5400

LICENSE PLATE BRACKET

A license plate mounting bracket shall be provided complete with a chrome-plated shielded indirect type light. Bracket shall be mounted at the rear of the apparatus body.

One (1)
NA-00-5600

BACKUP ALARM

An automatic, electronic reverse alarm shall be provided and installed. An alarm shall activate whenever the reverse gear is selected in the transmission.

The back up alarm to be an ECCO, Model SA917-PM2 which automatically adjusts its volume to maintain a minimum of five (5) dba above surrounding environmental noise levels.

One (1)
NA-00-6300

LOAD MANAGER

The apparatus shall be equipped with a Kussmaul model 091-79 Automatic Load Shedding System for performing continuous electrical load management. The Load Manager shall have the following features:

- Monitor 12-volt system and detect low voltage.
- Capability to control two (2) loads.
- Automatic reset when voltage rises.
- Adjustable voltage setpoint.

The load manager shall be protected against reverse polarity and shorted outputs, and be enclosed in a enclosure to enhance EMI/RFI protection. CSFA shall provide for all electrical loads in excess of the NFPA minimum electrical requirements that exceed the alternator output.

Five (5)
NA-01-1000

COMPARTMENT LIGHTING

All side and rear exterior equipment compartments shall be provided with one (1) clear compartment light mounted to the top of the compartment ceiling. Compartment lights shall switch on automatically when the compartment door is opened and switch off when the door is closed.

Rosenbauer – Central Division

One (1)
NA-01-3000

OPEN COMPARTMENT/HAZARD WARNING LIGHT

A red flashing, warning light shall be provided and installed in the driver's compartment to indicate an open passenger or apparatus compartment door. The hazard light shall also be attached to folding equipment racks and light towers as specified. Light shall be properly marked and identified.

One (1)
NB-02-5400

BATTERY DISCONNECT SWITCH

A Cole-Hersee M-284-01 heavy-duty battery disconnect switch shall be provided and mounted in a convenient location to the driver. All wiring shall be provided from the switch to the chassis supplied batteries.

A "Battery-On" pilot light shall be provided, visible to the driver.

IGNITION SWITCH

A non-removable ignition key shall be provided.

One (1)
NB-02-6200

BATTERY CONDITIONER

A 110-volt Kussmaul Auto-Charge 1000, single system, 18-amp, automatic battery charger and power supply shall be provided and installed within the chassis cab and wired to the battery system. Battery charger shall be 18-amp output type designed to automatically charge the battery system when shoreline power is connected. The charger shall be equipped with a bar graph type charge level indicator to indicate the charge rate. The charger shall have an electronic sensing circuit to sense the true battery voltage while eliminating the need for external sensor wires. Charging is completely automatic, when the battery is fully charged, all charging stops. There is no over charging and no water boil off.

The charger shall have a built in 3-amp battery saver for rechargeable hand lights.

The battery conditioner shall be located in the front left body compartment on the driver's side.

One (1)
NB-02-7615

AUTO-EJECT

A Kussmaul "Auto-Eject" automatic disconnect device shall be provided and installed on the 110-volt shoreline connection complete with weatherproof cover and matching plug. The Auto-Eject shall be activated by the chassis starter switch to disconnect the plug.

The shoreline plug shall be located in the driver's side step area.

Receptacle shall be a 120 volt, 15 amp (NEMA 5-15P).

Rosenbauer – Central Division

One (1)
NB-02-9100

DASH MOUNTED EMERGENCY ELECTRICAL SWITCH PANEL

An electrical switch panel shall be designed and mounted in the cab dash area. All switches shall be provided with back lighted snap-in legend inserts.

SWITCHES

All emergency light switches shall be lighted, rocker style. Switches shall be internally lit when the switch circuit is in the on position. A plug-in identification label is to be provided and installed adjacent to each rocker switch with backlighting provided behind the label.

An internally lighted "master" switch shall be provided and wired through a heavy-duty relay to activate power to the emergency lights.

Two (2) spare switches will be provided.

The switch locations and layout will be determined at the pre-construction conference.

One (1)
NB-03-2400

MAP LIGHT

One (1) flexible "gooseneck" type map light shall be provided and mounted on the cab dash panel complete with a switch on the light fixture base.

The light shall be mounted directly in front of the officer's seat.

One (1)
NB-10-5000

REAR STEP LIGHTS

Two (2) chrome plated lights shall be furnished and installed on the rear face of the body to illuminate the rear step area. Lights shall be wired to the panel light switch at the pump operator's panel.

One (1)
NB-10-5100

SIDE RUNNING BOARD LIGHTS

Two (2) flush mounted, chrome-plated lights shall be furnished and installed one on each side of the front face of the body to illuminate the step area. Lights shall be wired to the panel light switch at the pump operator's panel.

Two (2)
NB-10-5400

ENGINE COMPARTMENT WORK LIGHT

An engine compartment work light shall be provided complete with a switch mounted on the light head.

Two (2) engine compartment lights shall be provided.

Rosenbauer – Central Division

One (1)
NB-10-5600

PUMP COMPARTMENT WORK LIGHT

A pump compartment work light shall be provided and installed within the pump compartment area complete with a switch mounted on the light head.

One (1)
NB-10-6000

UNDER CAB LIGHTING

There shall be two (2) lights furnished below the chassis cab, one on each side below each door. The lights shall be wired to switch on and off automatically when the cab doors are opened.

One (1)
NB-10-6800

UNDER BODY LIGHTING

There shall be two (2) lights furnished below the pump house running board, one on each side. The lights shall be wired to turn on and off with a switch located on the pump operator's panel.

One (1)
NB-10-6900

UNDER BODY LIGHTING REAR STEP

There shall be two (2) lights furnished below the rear step, one on each side. The lights shall be wired to turn on and off with a switch located on the pump operator's panel.

One (1)
NB-30-0200

REAR DECK LIGHTS

Two (2) Unity #AG series, chrome-plated, six-inch rear mounted lights with swivel type mounting bracket and individual switches shall be provided.

One light shall be a **35-watt 75,000 candlepower spot** lamp, and one light shall be a **35-watt 1,100 candlepower flood** lamp.

Two (2)
NB-30-1100

REAR SCENE LIGHT

There shall be a Weldon Model 2010, 12-volt 50-watt Scenelight provided and mounted at the rear of the body. Light shall be mounted on an 18-degree downward angled, polished aluminum casting. The light shall be wired through a switch in the chassis cab and be labeled "Rear Scene Light".

Two (2) rear scene lights shall be provided.

Two (2)
NB-30-1200

DRIVER SIDE SCENE LIGHT

There shall be a Weldon Model 2010, 12-volt 50-watt Scenelight provided and mounted on the driver side of the body. Light shall be mounted on an 18-degree downward angled, polished aluminum casting. The light shall be wired through a switch in the chassis cab and be labeled "Driver's Side Scene Light".

Two (2) scene lights shall be provided and mounted at the front and rear of the body on the driver's side.

Rosenbauer – Central Division

Two (2)
NB-30-1300

PASSENGER SIDE SCENE LIGHT

There shall be a Weldon Model 2010, 12-volt 50-watt Scenelight provided and mounted on the passenger side of the body. Light shall be mounted on an 18-degree downward angled, polished aluminum casting. The light shall be wired through a switch in the chassis cab and be labeled "Passenger's Side Scene Light".

Two (2) scene lights shall be provided and mounted at the front and rear of the body on the passenger's side.

One (1)
NB-40-0600

TRAFFIC DIRECTION BAR

A Whelen Model TA-837A Traffic Advisor light bar, 44" long with eight twist-lock, halogen modules, shall be provided and mounted facing the rear of the apparatus with control console mounted in the truck cab.

One (1)
NB-40-0930

SURFACE MOUNTED TRAFFIC ADVISOR WITH SHIELD

The traffic advisor shall be surface mounted on the rear of the apparatus body. There shall be a shield installed directly above the traffic advisor that is approximately the same width and depth as the traffic advisor.

One (1)
NC-02-9010

AIR HORNS

Two (2) chrome-plated Grover "Stuttertone" air horns shall be provided and recess mounted in the front bumper extension. A pressure protection valve to prevent the use of air horns or other air operated accessories when the system air pressure drops below 80 psi shall be provided.

Air horns shall be controlled from the following switch positions.

One (1)
NC-02-9025

One (1) foot switch shall be provided on the driver's side floor for activation of the air horn.

One (1)
NC-03-2000

ELECTRONIC SIREN

A Code 3 Model 3692 V-CON, 200-watt electronic siren with Hi-Lo and hardwired microphone shall be provided and mounted in the cab.

One (1)
NC-03-3000

HORN SELECTOR SWITCH

A siren/horn selector switch shall be provided and mounted on the switch console to select activation of the chassis horn, or the siren from the steering wheel horn control.

Rosenbauer – Central Division

One (1)
NC-03-5100

SPEAKER

A Code 3 PB100C, 100-watt speaker shall be provided and recess mounted in the front bumper of the chassis. The speaker shall be connected to the electronic siren control unit.

One (1)
NC-04-2900

RED LIGHT

There shall be a steady burning red light furnished on the chassis cab.

One (1)
NE-04-0950

EMERGENCY LIGHTING

The upper and lower zones "A", "B", "C", and "D" of the apparatus shall have the following emergency lighting equipment:

One (1)
NE-04-5800

LIGHT BAR

One (1) Code 3 model 5300AL 56" mounted on chassis cab roof to meet the NFPA upper zone A lighting requirement. Light bar to have the following equipment.

- (6) 50-watt standard rotators
- (1) 50-watt fast rotator
- (2) diamond mirrors
- (2) 2-step cascade mirrors
- (1) 50-watt stationary light (to meet California DMV requirements)

To meet NFPA requirements the three (3) inboard rotators will be load managed when the parking brake is set.

One (1)
NE-05-1000

REAR LIGHTS

Four (4) Code 3 model 81X 9"x 7" flashing halogen lights mounted on rear upper corners of body to meet the NFPA Zone B, C, D upper level lighting requirement. The lights shall be activated through the master emergency light switch located on the electrical console. Two (2) on rear, one (1) on each side with the following equipment.

- (1) 50-watt halogen bulb.
- (1) Flasher assembly.
- Red lens on each.

One (1)
NE-05-3000

ZONE A FRONT LIGHTS

There shall be two (2) Code 3 model OL135 oscillating lights furnished on the front grill to meet the NFPA Zone A lower level lighting requirement. The lights shall be connected to a relay be activated through the master emergency light switch located on the electrical console.

Rosenbauer – Central Division

One (1)
NE-05-4600

ZONE B & D SIDE LIGHTS

There shall be three (3) Code 3 model 4135BZ halogen flashing lights with bezels furnished on each side of the apparatus to meet the NFPA Zone B & D lower level lighting requirement. One light mounted as far forward as possible, one light mounted as far to the rear as possible, and one light mounted between the front and rear lights. The halogen lights shall be connected to a flasher and be activated through the master emergency light switch located on the electrical console.

One (1)
NE-05-7600

ZONE C REAR LIGHTS

There shall be two (2) Code 3 model 8135 halogen flashing lights furnished on the rear of the apparatus body to meet the NFPA Zone C lower level lighting requirement. The halogen lights shall be connected to a flasher and be activated through the master emergency light switch located on the electrical console.

One (1)
NS-00-0100

12 VOLT ELECTRICAL CERTIFICATION

The low voltage electrical system shall be tested and certified per NFPA 1901 requirements.

A certificate of compliance shall be provided with the completed vehicle upon delivery.

Minimum electrical load consists of the total amperage required to simultaneously operate the following in a stationary mode at the incident scene.

- The propulsion engine and transmission.
- All Clearance and marker lights.
- The communication radio. (Default of 5.0 amps used for testing).
- Illumination of all walking surfaces, the ground at all egress points, controls and instrument panels and 50% of the total compartment lighting load.
- Minimum warning lights required for "Blocking Right of Way" mode.
- The current to simultaneously operate any fire pump, aerial device & hydraulic pumps.
- Anything defined by the purchaser to be critical to the mission of the apparatus.

The first test for the electrical system is the **Reserve Capacity Test**. All the above listed components operate with the engine shut off. After 10 minutes all electrical loads are shut off and the battery system must have adequate reserve power to start the engine.

The second test is the **Alternator Performance Test at Idle**. All the above listed components operate with the engine at an idle. There can be no current draw from the batteries of the apparatus.

The third test is the **Alternator Performance Test at Full Load**. All electrical components shall be activated with the engine operating at governed RPM for two hours. During the test the system voltage can not drop below 11.7-volts or have excessive battery discharge for more than 120 seconds. Any loads not listed in the minimum electrical load may be load managed in order to pass the test.

All of the above tests must be conducted with the engine compartment at approximately 200 degrees.

Rosenbauer – Central Division

One (1)
PA-01-0003

PAINTING

All bright metal fittings if unavailable in stainless steel shall be heavily chrome-plated. Iron fittings shall be copper plated prior to chrome plating.

All seams shall be caulked both inside and along the exterior edges with an automotive sealant to prevent moisture from entering between any body panels.

The body and all parts shall be thoroughly washed with grease cutting solvents prior to any sanding. After the body has been sanded and the minor imperfections filled and sanded, the body shall be washed again with a solution to remove any contaminants on the surface. The first coating to be applied is a self-etching primer for maximum adhesion to the body metal. The next three coats shall be an acrylic, urethane, primer surfacer. The primer surfacer coat is to be hand sanded with 600-grit sandpaper to insure maximum gloss of the paint. The last step is the application of at least three coats of Concept Acrylic Urethane two component color.

The fire pump and all rigid discharge and suction plumbing shall be painted silver in color.

While constructing the truck body, all aluminum parts shall be properly fitted on the body. The backside of all aluminum parts shall be sanded smooth of any burrs and sharp edges.

All aluminum parts shall be bolted to the body using stainless steel fasteners. Cadmium plated fasteners are not acceptable.

During reassembly of the apparatus, care shall be exercised in fitting and fastening the parts back in their respective position on the vehicle.

One (1)
PA-01-0200

UNDERCOATING

The body sub frame shall be undercoated with a heavy-duty automotive type undercoating before the rubber backing and the compartments are attached. After the body has been attached to the sub frame and all final items have been installed the entire body assembly shall be undercoated

One (1)
PA-01-1515

INTERIOR COMPARTMENT PAINT

The interior vertical compartment walls are to be painted white with a black colored spatter finish material.

One (1)
PA-01-3500

WHEEL PAINTING

The exterior faces of the front and rear wheels, shall be finished painted to match the apparatus body. Wheels shall be properly prepared and finished with primer coats and topcoats as specified.

The outer two-inches of each outside wheel rim shall be painted Silver in color, unless otherwise specified.

Rosenbauer – Central Division

One (1)
PA-01-5500

TWO TONE CAB PAINT

The chassis cab exterior shall be two-tone finish painted. The area to be painted shall be sanded and thoroughly prepared then refinished with PPG Concept paint.

The upper color to be white.
The lower color to be red

Exact paint colors will be determined during the pre-construction conference.

One (1)
PA-02-1910

LETTERING

Lettering shall be done in gold leaf mylar letters, shaded in black, and encapsulated in clear mylar. Lettering to be placed on each cab door as directed by fire department. Maximum of fifty (50) letters.

One (1)
PA-02-2600

LETTERING SHALL BE AS FOLLOWS

Exact lettering requirements shall be determined prior to construction.

One (1)
PA-02-6000

REFLECTIVE SAFETY STRIPE

A 8" wide 3M brand Scotchlite #680-10 reflective stripe shall be affixed to the perimeter of the vehicle. Striping shall be placed up to 60" above ground level and shall conform to NFPA reflectivity requirements. At least 60% of the perimeter length of each side and width of the rear, and at least 40% of the perimeter width of the front of the vehicle shall have reflective stripe.

The stripe shall be white in color.

One (1)
PC-00-0100

IDENTIFICATION & SAFETY LABELS

A permanent plate shall be installed in the driver's compartment to specify the quantity and type of the following fluids in the vehicle:

1. Engine oil.
2. Engine coolant.
3. Transmission fluid.
4. Pump Transmission Lubrication Fluid.
5. Pump Primer Fluid (If applicable).
6. Drive Axle Lubrication Fluid.
7. Air-conditioning refrigerant.
8. Air-conditioning lubrication oil.
9. Power steering fluid.
10. Transfer case fluid.
11. Equipment rack fluid.
12. Air compressor system lubricant.
13. Generator system lubricant.

Rosenbauer – Central Division

When trucks have been UL certified, a permanent plate with pump performance data and serial numbers shall be installed on the pump panel.

A permanent plate shall be installed in the driver's compartment specifying the maximum number of personnel the vehicle is designed to carry per NFPA standards. It shall be located in an area visible to the driver.

An accident prevention sign stating "DANGER PERSONNEL MUST BE SEATED AND SEAT BELTS MUST BE FASTENED WHILE VEHICLE IS IN MOTION OR DEATH OR SERIOUS INJURY MAY RESULT". The warning sign shall be placed so it is visible from all seating positions.

An accident prevention sign stating "DANGER DO NOT RIDE ON REAR STEP WHILE VEHICLE IS IN MOTION, DEATH OR SERIOUS INJURY MAY RESULT". The warning sign shall be placed so it is visible from the rear step of the vehicle.

If an inlet located at the pump operator's position is valved, it shall be provided with a permanent label that states "WARNING SERIOUS INJURY Or DEATH COULD OCCUR IF INLET IS SUPPLIED BY A PRESSURIZED SOURCE WHEN THE VALVE IS CLOSED".

One (1)
TA-01-0100

OPERATION / SERVICE MANUALS

The manufacturer shall provide with the vehicle upon delivery, one (1) complete delivery manual. These manuals shall be in a notebook type binder, with reference tabs for each section of the vehicle. Within each section shall be:

1. Individual component manufacturer instruction and parts manuals.
2. Warranty forms for body.
3. Warranty forms for all major components.
4. Warranty instructions and format to be used in compliance to warranty obligations.
5. Wiring diagrams.
6. Installation instructions and drawings for major parts.
7. Visual graphics, electronic photos of installations of major parts.
8. Necessary normal routine service forms, publications and components of body portion of the apparatus.
9. Technical publications on training and instructions for major body components.
10. Warning and safety related notices for personnel protection.
11. Cab and chassis manuals on parts, service and maintenance shall be provided.
12. UL Pump Certification sheets, including the Manufacturer's Record of Apparatus construction details.
13. Certificate of Compliance to Electrical Warning System Low Voltage test.
14. Line Voltage Electrical System test certificate.
15. Water tank capacity certificate.

Rosenbauer – Central Division

One (1)
VA-00-0000

ADDITIONAL EQUIPMENT

The following equipment shall be furnished by the apparatus body builder.

Two (2)
VA-03-3000

HARD SUCTION HOSE

10-foot length of 4" lightweight PVC, flexible fire department suction hose, first quality non-collapsible type, of a design having a low friction loss and which will not collapse under a vacuum of 23".

Hard suction hose to be equipped with lightweight couplings. Long handles on female and rocker lugs on male couplings.

Two (2) lengths of 4" x 10 ft. suction hoses shall be provided.

One (1)
VA-04-1300

SUCTION STRAINER

A 4" NST chrome-plated barrel type suction hose strainer shall be provided.

One (1)
VA-04-4400

FOLDING TANK

There shall be a portable-folding tank furnished with the apparatus. The folding tank shall have a welded steel frame with a 22-ounce vinyl liner.

The folding tank shall have capacity of 4000 US gallons.

One (1)
VA-05-9300

MISCELLANEOUS HARDWARE

There shall be a bag of miscellaneous hardware included with the apparatus. This bag shall contain nuts and bolts that are commonly used on the apparatus.